

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/043775 A1

(51) International Patent Classification⁷: B63B 3/38

(21) International Application Number:
PCT/GB2003/004918

(22) International Filing Date:
12 November 2003 (12.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0226443.0 13 November 2002 (13.11.2002) GB

(71) Applicant (for all designated States except US): GIBBS
TECHNOLOGIES LIMITED [GB/GB]; Avenue Road,
Nuneaton, Warwickshire CV11 4LY (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): JENKINS, Nell,
Graham [GB/GB]; Gibbs Technologies Limited, Avenue
Road, Nuneaton, Warwickshire CV11 4LY (GB).

(74) Agents: CHURCH, Simon, John et al.; Marks & Clerk,
144 New Walk, Leicester LE1 7JA (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:



— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: FLEXIBLE KEEL AND FITTING THEREFOR



(57) Abstract: Water craft or amphibious vehicle (10, fig. 1), comprises hull (12) fitted with at least one elongate longitudinal keel (16, 42); which may be extruded from rubber. The keel has at least one mounting formation (24, 44), to engage with channel formation (22, 41). The keel may be mounted directly into hull (12); alternatively, at least one mounting structure may comprise an extrusion (34, 36) (or 30, fig. 4); mounted into a channel (38) (or 28, fig. 4) in the hull. The keel may be flexible to resist damage if grounded; but is laterally stiff to aid handling on water. The keel may be slid into place longitudinally; and may be finished with a rubber end piece, protected by a further metal end piece (18, 20, fig. 2). Both end pieces may be detachable. Keel (16) may be foam filled; or may be inflated with fluid to alter its cross section.

WO 2004/043775 A1